


MODEL: BF-V550-60

440V | 1800rpm | 60Hz



ESP Standby Power	564kVA	PRP Prime Power	512kVA
ENGINE	Volvo TAD1346GE	ALTERNATOR	STAMFORD S5L1D-C41

GENERAL FEATURES

Engine: Volvo TAD1346GE

Alternator: single bearing, IP23, insulation class H

55°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

**MODEL: BF-V550-60****440V | 1800rpm | 60Hz****GENERATOR RATINGS**

Voltage	Hz	Phase	PF (COS Φ)	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
480/277	60	3	0.8	678	451kW/564kVA	410kW/512kVA
460/266	60	3	0.8	708	451kW/564kVA	410kW/512kVA
440/254	60	3	0.8	740	451kW/564kVA	410kW/512kVA
416/240	60	3	0.8	783	451kW/564kVA	410kW/512kVA

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO 8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

SALES PROMISES

Baifa Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: 15 months from the date BAIFA sold to the first buyer or one year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from Baifa Power or distributors in your location.

MODEL: BF-V550-60
440V | 1800rpm | 60Hz

ENGINE SPECIFICATION

Manufacturer / Model	Volvo TAD1346GE
Air intake system	Turbocharged, Air/Air inter cooling
Fuel system	Elec. Injection, Elec. Fuel System
Cylinder arrangement	6 in line
Displacement	12.78L
Bore and stroke	131×158 mm
Compression ratio	17.8.1
Rated speed	1800rpm
Max. Standby power at rated speed	479kW
Governor type	ECU EMS2

Exhaust System

Exhaust gas flow	86.8 m ³ /min
Exhaust temperature	431°C
Max back pressure	10kPa

Air Intake System

Max intake restriction	5kPa
Combustion air flow	37.6 m ³ /min
Air flow required for radiator	432 m ³ /min

**MODEL: BF-V550-60****440V | 1800rpm | 60Hz****Fuel System**

Fuel consumption @ 100% (Prime Power) Load	196g/kWh	105L/h
Fuel consumption @ 75% (Prime Power) Load	200g/kWh	81L/h
Fuel consumption @ 50% (Prime Power) Load	201g/kWh	56L/h

Oil System

Total oil capacity	36L
Oil consumption	0.03L/h
Oil sump capacity	19-30L

Cooling System

Coolant capacity	48L
Max water temperature	107°C



MODEL: BF-V550-60

440V | 1800rpm | 60Hz

ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	<50
THF	<2%
Alternator Capacity	550kVA
Alternator Efficiency	94.1%



MODEL: BF-V550-60

440V | 1800rpm | 60Hz

GENERATING SET DATA

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +20\%$
Transient voltage deviation (sudden power increase)	$\leq -15\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 4S$
Voltage recovery time (sudden power increase)	$\leq 4S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 0.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +10\%$
Transient frequency deviation (sudden power increase)	$\leq -7\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 3S$
Frequency recovery time (sudden power increase)	$\leq 3S$

STANDARD FEATURES

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	MCCB

MODEL: BF-V550-60

440V | 1800rpm | 60Hz

OPTIONS

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		


DIMENSIONS & WEIGHT



Standard Configuration (open type)

Overall Dimensions: 3230×1200×1830 mm

Weight: 3210 kg



Soundproof Type

Overall Dimensions: 4230×1460×2150 mm

Weight: 4650 kg

Specifications are subject to change without notice.

BAIFA POWER (WUXI) LTD.

WEBSITE: WWW.BAIFAPOWER.COM

EMAIL: MARKETING@BAIFAPOWER.COM

TEL: +86-510-85342633

Comprehensive Solutions For
POWER GENERATION