

**MODEL: BF-V340**

**400V | 1500rpm | 50Hz**



**ESP**

Standby Power

**340 kVA**

**PRP**

Prime Power

**310 kVA**

**ENGINE**

**VOLVO**

**TAD1341GE**

**ALTERNATOR**

**STAMFORD**

**S4L1D-D41**

## GENERAL FEATURES

Engine: VOLVO TAD1341GE

Alternator: single bearing, IP23, insulation class H

55°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

**MODEL: BF-V340****400V | 1500rpm | 50Hz**

## GENERATOR RATINGS

Voltage	Hz	Phase	PF ( COS $\Phi$ )	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
440/254	50	3	0.8	446	272/340	252/310
415/240	50	3	0.8	473	272/340	252/310
400/230	50	3	0.8	490	272/340	252/310
380/220	50	3	0.8	516	272/340	252/310

**Prime Power (PRP):** Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

**Standby Power Rating (ESP):** The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

## SALES PROMISES

Baifa Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: 15 months from the date BAIFA sold to the first buyer or one year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from Baifa Power or distributors in your location.

**MODEL: BF-V340****400V | 1500rpm | 50Hz****ENGINE SPECIFICATION**

Manufacturer / Model	VOLVO/TAD1341GE
Air intake system	Turbocharged, Air/Air inter cooling
Fuel system	Elec. Injection, Elec. Fuel System
Cylinder arrangement	6 in line
Displacement	12.78L
Bore and stroke	131*158 (mm)
Compression ratio	18.1
Rated speed	1500rpm
Max. Standby power at rated speed	302KW/411HP (with fan)
Governor type	EMS2

**Exhaust System**

Exhaust gas flow	52 m <sup>3</sup> / min
Exhaust temperature	414℃
Max back pressure	10 kPa

**Air Intake System**

Max intake restriction	5 kPa
Combustion air flow	24.1 m <sup>3</sup> /min
Air flow required for radiator	264 m <sup>3</sup> /min

**MODEL: BF-V340****400V | 1500rpm | 50Hz****Fuel System**

Fuel consumption @ 100% (Prime Power) Load	191 g/kWh	61.3L/h
Fuel consumption @ 75% (Prime Power) Load	194 g/kWh	46.6L/h
Fuel consumption @ 50% (Prime Power) Load	200 g/kWh	32.4L/h

**Oil System**

Total oil capacity	36L
Oil consumption	0.04L/h
Oil sump capacity	19~30L

**Cooling System**

Coolant capacity	44 L
Max water temperature	107°C

**MODEL: BF-V340****400V | 1500rpm | 50Hz**

## ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

### Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	<50
THF	<2%
Alternator Capacity	310kVA
Alternator Efficiency	92.9%

**MODEL: BF-V340****400V | 1500rpm | 50Hz**

## GENERATING SET DATA

Related range of voltage setting	$\geq \pm 5\%$
----------------------------------	----------------

Steady-state voltage deviation	$\leq \pm 1\%$
--------------------------------	----------------

Transient voltage deviation (100 % sudden power decrease)	$\leq +20\%$
---	--------------

Transient voltage deviation (sudden power increase)	$\leq -15\%$
---	--------------

Voltage recovery time (100 % sudden power decrease)	$\leq 4S$
---	-----------

Voltage recovery time (sudden power increase)	$\leq 4S$
---	-----------

Related range of frequency setting	0-5% adjustable
------------------------------------	-----------------

Steady-state frequency band	$\leq 0.5\%$
-----------------------------	--------------

Transient frequency deviation (100 % sudden power decrease)	$\leq +10\%$
---	--------------

Transient frequency deviation (sudden power increase)	$\leq -7\%$
---	-------------

Frequency recovery time (100 % sudden power decrease)	$\leq 3S$
---	-----------

Frequency recovery time (sudden power increase)	$\leq 3S$
---	-----------

## STANDARD FEATURES

Standard auto control system

Exhaust system (including until muffler)

Documents

Oil drain valve

Starting batteries (maintenance-free &amp; watering-free) with connective wires

Special coolant

MCCB

**MODEL: BF-V340**

**400V | 1500rpm | 50Hz**

## OPTIONS

Daily fuel tank

Rainproof type

Remote control panel

Alternator heater

Soundproof type

Paralleling system

Spare parts

Trailer type

Switch box

Automatic transfer switch


## DIMENSIONS & WEIGHT



### Standard Configuration (open type)

Overall Dimensions: 3050×1200×1830 mm

Weight: 2250 kg



### Soundproof Type

Overall Dimensions: 3890×1460×2150 mm

Weight: 3790 kg

*Specifications are subject to change without notice.*

**BAIFA POWER (WUXI) LTD.**

**WEBSITE: [WWW.BAIFAPOWER.COM](http://WWW.BAIFAPOWER.COM)**

**EMAIL: [MARKETING@BAIFAPOWER.COM](mailto:MARKETING@BAIFAPOWER.COM)**

**TEL: +86-510-85342633**

Comprehensive Solutions For  
**POWER GENERATION**