nins	Engine Performance Data	G-Drive	Date				
cumm	Cummins Inc.	Inc. 05713_C11		1-Mar-21			
	Columbus, Indiana 47202-3005	00215-011	Configuration	CPL	Revision		
	http://www.cummins.com	FR21289	D0C3004GX03	5702	0		
Compression Ratio	<b>b</b> 17	Displacement	793 in³ (13 L)				
Fuel System	XPI	Aspiration	Turbocharged and Charge Air Cooled		oled		
Aftertreatment	N/A	Emission Certification	Non Certified, Non Certified, Non Certified				

Engine Speed	Standby Power		Prime	Power	Continuous Power		
rpm	kWm	bhp	kWm	bhp	kWm	bhp	
1500	N/A	N/A	N/A	N/A	N/A	N/A	
1800	562	754	512	686	N/A	N/A	

## Engine Fluid Consumption @ 1500 rpm

Ou	tput Pov	ver	Fuel DEF		DEF		
%	kWm	bhp	kg/kWm-hr	lb/bhp-hr	L/hr	US gal/hr	L/hr
Standb	y Power						
100	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Prime Power							
100	N/A	N/A	N/A	N/A	N/A	N/A	N/A
75	N/A	N/A	N/A	N/A	N/A	N/A	N/A
50	N/A	N/A	N/A	N/A	N/A	N/A	N/A
25	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Continuous Power							
100	N/A	N/A	N/A	N/A	N/A	N/A	N/A



## Engine Fluid Consumption @ 1800 rpm

Ou	Itput Pov	ver		Fuel				
%	kWm	bhp	kg/kWm-hr	kg/kWm-hr lb/bhp-hr L/hr		US gal/hr	gal/hr	
Standby Power								
100	562	754	0.197 0.324 134 34.4		N/A			
Prime Power								
100	512	686	0.195	0.321	121	31.0	0.0	
75	384	515	0.195	0.321	91	23.3	0.0	
50	256	343	0.198	0.326	61	15.7	0.0	
25	128	172	0.218	0.359	34	8.7	0.0	
Continuous Power								
100	#######	N/A	0.000	0.000	#VALUE!	#VALUE!	0.0	



### Data Subject to Change Without Notice

Data shown above represent gross engine performance capabilities obtained and corrected in accordance with ISO-3046 conditions of 100 kPa (29.53 in Hg) barometric pressure [110 m (361 ft) altitude], 25 °C (77 °F) air inlet temperature, and relative humidity of 30% with No. 2 diesel or a fuel corresponding to ASTM D2.

erates shown are based on in H2O air intake restriction and in Hg exhaust back pressure.

The fuel consumption data is based on No. 2 diesel fuel weight at 0.85 kg/L (7.1 lbs/US gal). Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan, optional equipment and driven components.

Data Status : Limited Production Tolerance : +/- 10% Chief Engineer: Michael P Hurt

STANDEY FOWER RATING: Applicable for supplying emergency power for the duration of the utility power outage. No overload capability is available for this rating. Under no condition is an engine allowed to operate in parallel with the public utility at the Standby Power rating. This rating should be applied where reliable utility power is available. A Standby rated engine should be sized for a Max of an 80% average load factor and 200 hours of operation per year. This includes less than 25 hours per year at the Standby Power rating. Standby rating should hereve the applied except in true emergency power outages. Negotiated power outages contracted with a utility company are not considered an emergency. <u>PRIME POWER RATING</u>: Applicable for supplying electric powe in lieu of commercially purchased power. Prime Power applications must be in the form of one of the following two categories: <u>UNLIMITED TIME RUNNING PRIME POWER</u>; Prime Power is available for an unlimited number of hours per year in a variable load application. Variable load should not exceed a 70% average of the Prime Power rating during any operating period of 250 hours. The total operating time at 100% Prime Power shall not exceed 500 hours per year. A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation. Total operating time at the 10% overload power shall not exceed 25 hours per year. <u>LIMITED TIME RUNNING PRIME POWER</u>; Limited Time Prime Power is available for a limited number of hours in a nonvariable load application. It is intended for use in situations where power outages are contracted, such as in utility power cutaliment. Engines may be operated in parallel to the public utility up to 750 hours per year at power levels never to exceed the Prime Power rating. The customer should be aware, however, that the life of any engine will be reduced by this constant high load operation. Any operation exceeding 750 hours per year at the Prime Power rating should use the Continuous Power rating

es have been formulated to ensure proper application of generator drive engines in A.C. generator set installation

© 2021, Cummins Inc., All Rights Reserved Cummins Confidential and Proprietary Controlled copy is located on gce.cummins.com



77 °F (25 °C)

### **Operation At Elevated Temperature And Altitude:**

For <u>Standby Operation</u> above these conditions, derate by an additional N/A% per 1,000 ft (305 m), and N/A% per 18 °F (10 °C). For <u>Prime Operation</u> above these conditions, derate by an additional N/A% per 1,000 ft (305 m), and N/A% per 18 °F (10 °C). For <u>Continuous Operation</u> above these conditions, derate by an additional N/A% per 1,000 ft (305 m), and N/A% per 18 °F (10 °C).

#### **Operation At Elevated Temperature And Altitude:**

For <u>Standby Operation</u> above these conditions, derate by an additional N/A% per 1,000 ft (305 m), and N/A% per 18 °F (10 °C). For <u>Prime Operation</u> above these conditions, derate by an additional N/A% per 1,000 ft (305 m), and N/A% per 18 °F (10 °C). For <u>Continuous Operation</u> above these conditions, derate by an additional N/A% per 1,000 ft (305 m), and N/A% per 18 °F (10 °C).

# FR21289 (Continued) Page 3

# **General Engine Data**

Installation Drawing Number			N/A
Туре		Four Cycle	; Inline; 6 Cylinder
Aspiration		Turbocharged a	and Charge Air Cooled
Bore x Stroke	in x in (mm x mm)	5.12 x 6.42	(130 x 163)
Displacement	in <sup>3</sup> (L)	793	(13)
Compression Ratio			17
Dry Weight (Approximate)	lbm (kg)	2745	(1245)
Wet Weight (Approximate)	lbm (kg)	2888	(1310)
Aftertreatment Weight (Approximate)	lbm (kg)	N/A	(N/A)
Moment of Inertia of Rotating Components			
with FW 2350 Flywheel, SAE 01	in • lbf • sec² (kg • m²)	16.8	(1.9)
Center of Gravity from Rear Face of Block	in (mm)	18.07	(459)
Center of Gravity Above Crankshaft Centerline	in (mm)	7.91	(201)
Engine Mounting			
Max Bending Moment at Rear Face of Block	lb • ft (N • m)	1000	(1356)
Exhaust System			
Max Allowable Static Bending Moment @ Exhaust Outlet Flange	lb • ft (N • m)	14	(19)
Max Back Pressure, Standby Power, Turbo Outlet (1500/1800rpm)	in Hg (kPa)	N/A / 3.8	(N/A / 13)
Air Induction System			
Max Intake Air Restriction			
With Normal Duty Air Cleaner and Clean Filter Element	in H <sub>2</sub> O (kPa)	15	(3.7)
With Heavy Duty Air Cleaner and Clean Filter Element	in H <sub>2</sub> O (kPa)	N/A	(N/A)
With Dirty Filter Element	in H <sub>2</sub> O (kPa)	25	(6.2)
Maximum allowable air temperature rise over ambient at Turbo Compressor inlet (Turbo-charged Engines):	Δ°F (Δ°C)	20	(11.1)
Cooling System			
Jacket Water/ High Temperature Circuit Requirements			
Max Coolant Friction Head External to Engine (1500/1800 rpm)	psi (kPa)	N/A / 10.2	(N/A / 70)
Engine Water Flow at Stated Friction Head External to Engine:			
-5psi- 5 psi Friction Head (1500/1800 rpm)	US gpm (L/m)	N/A / 133	(N/A / 503)
Maximum Friction Head (1500/1800 rpm)	US gpm (L/m)	N/A / N/A	(N/A / N/A)
Coolant Capacity - Engine	US gal (L)	6.1	(23.1)
Minimum Pressure Cap Rating at Sea Level	psi (kPa)	15	(103)
Max Static Head of Coolant Above Crankshaft Centerline	ft (m)	46	(14)
Max Coolant (Top Tank) Temperature for Standby/Prime Power	°F (°C)	216 / 216	(102 / 102)
Thermostat (Modulating) Range	°F (°C)	180 - 201	(82 - 94)
Max Intake Manifold Temp Warning/Shutdown	°F (°C)	185 / 198	(85 / 92)
Low Temperature Circuit (LTC) Requirements			
Max Coolant Friction Head External to Engine (1500/1800 rpm)	psi (kPa)	N/A / N/A	(N/A) / N/A)
Aftercooler Water Flow at Stated Friction Head External to Engine:			
2.5 psi Friction Head (1500/1800 rpm)	US gpm (L/m)	N/A / N/A	(N/A / N/A)
Maximum Friction Head (1500/1800 rpm)	US gpm (L/m)	N/A / N/A	(N/A / N/A)
Max Coolant Temp into LTC @ 77°F (25°C) Ambient	°F (°C)	N/A	(N/A)
Max Coolant Temperature into LTC @			
Limiting Ambient Conditions for Standby/Prime Power	°F (°C)	N/A / N/A	(N/A) / N/A)
Thermostat (Modulating) Range	°F (°C)	N/A - N/A	(N/A) - N/A)
Coolant Capacity - Aftercooler	US gal (L)	N/A	(N/A)
Charge Air Cooler Requirements			
Max Allowable Pressure Drop Across Charge Air Cooler and OEM CAC piping (1500/1800 rpm)	in Hg (kPa)	N/A / 3.8	(N/A / 13)
Max Charge Air Cooler Outlet to Ambient at 77°F (25°C)(CAC dT)	Δ°F (Δ°C)	45	(25)

# FR21289 (Continued) Page 4

			· · · ·
Lubrication System			
Oil Pressure at Minimum Idle Speed	psi (kPa)	12	(83)
Oil Pressure at Governed Speed	psi (kPa)	30 - 41	(207 - 286)
Max Oil Temperature	°F (°C)	257	(125)
Oil Capacity with OP 2180: Low - High	US gal (L)	16.2 - 19.9	(61.2 - 75.3)
Total System Capacity (With Combo Filter)	US gal (L)	20.6	(78)
Fuel System			
Max Fuel Supply Restriction at Fuel Pump Inlet (clean/dirty filter)	in Hg (kPa)	5.0 / 8.0	(16.9 / 27)
Max Allowable Head on Injector Return Line			
(Consisting of Friction Head and Static Head)	in Hg (kPa)	8	(27)
Max Fuel Inlet Temperature	°F (°C)	160	(71)
Max Supply Fuel Flow (1500/1800 rpm)	US gph (L/hr)	N/A / 65	(N/A / 247)
Max Return Fuel Flow (1500/1800 rpm)	US gph (L/hr)	N/A / 30	(N/A / 114)
Electrical System			
System Voltage	volts	24	N/A
Minimum Recommended Battery Capacity			
Cold Soak @ 0 °F (-18 °C)	CCA	1250	N/A
Max Starting Circuit Resistance	ohm	0	0.002
Max Current Draw of the System	Amps	2000	2000
Cold Start Capability			
Unaided Cold Start			
Minimum Cranking Speed	rpm	150	
Minimum Ambient Temp for Unaided Cold Start	°F (°C)	32	(0)

### **Performance Data**

		STANDBY		PR	IME	CONTINUOUS		
		60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	
Governed Engine Speed	rpm	1800	N/A	1800	N/A	1800	N/A	
Engine Idle Speed	rpm	700-1200	N/A	700-1200	N/A	700-1200	N/A	
Gross Engine Power Output	bhp (kW)	754 (562)	N/A (N/A)	686 (512)	N/A (N/A)	#VALUE!	N/A (N/A)	
Brake Mean Effective Pressure	psi (kPa)	418 (2883)	N/A (N/A)	380 (2623)	N/A (N/A)	#VALUE!	N/A (N/A)	
Friction Power	hp (kW)	60 (45)	N/A (N/A)	60 (45)	N/A (N/A)	#VALUE!	N/A (N/A)	
Intake Air Flow	ft <sup>3</sup> /min (L/sec)	1303 (615)	N/A (N/A)	1271 (600)	N/A (N/A)	0 (0)	N/A (N/A)	
Exhaust Gas Temp	°F (°C)	1011 (544)	N/A (N/A)	930 (499)	N/A (N/A)	0 (-18)	N/A (N/A)	
Exhaust Gas Flow	ft <sup>3</sup> /min (L/sec)	3896 (1838)	N/A (N/A)	3651 (1723)	N/A (N/A)	0 (0)	N/A (N/A)	
Air:Fuel Ratio		22.5:1	N/A	24.3:1	N/A (N/A)	0:1	N/A (N/A)	
Radiated Heat to Ambient	BTU/min (kW)	3036 (53)	N/A (N/A)	2742 (48)	N/A (N/A)	#VALUE!	N/A (N/A)	
Heat to JW Radiator	BTU/min (kW)	11203(197)	N/A (N/A)	10196(178)	N/A (N/A)	0 (0)	N/A (N/A)	
Heat to Exhaust	BTU/min (kW)	24746(432)	N/A (N/A)	21653(378)	N/A (N/A)	0 (0)	N/A (N/A)	
* Heat to Fuel	BTU/min (kW)	286 (5)	N/A (N/A)	286 (5)	N/A (N/A)	0 (0)	N/A (N/A)	
Heat to Aftercooler Radiator	BTU/min (kW)	6301(110)	N/A (N/A)	5957(104)	N/A (N/A)	0 (0)	N/A (N/A)	
Charge Air Flow	lb/min (kg/min)	93 (42)	N/A (N/A)	91 (41)	N/A (N/A)	0 (0)	N/A (N/A)	
Turbo Comp Outlet Pressure	psi (kPa)	31 (215)	N/A (N/A)	29 (199)	N/A (N/A)	0 (0)	N/A (N/A)	
Turbo Comp Outlet Temp	°F (°C)	404 (207)	N/A (N/A)	395 (202)	N/A (N/A)	0 (-18)	N/A (N/A)	

\* This is the maximum heat rejection to fuel.

## **Noise Emissions**

Freque Sound Pov	ncy (Hz) ver dB(A) <sup>123</sup>	63	125	250	500	1000	2000	4000	8000	Overall
1500 rpm	Engine <sup>4</sup>	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
50 Hz	Exhaust <sup>5</sup>	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
1800 rpm	Engine <sup>4</sup>	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
60 Hz	Exhaust <sup>5</sup>	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

1. The test figures quoted are from a single gen-set test and do not constitute a guarantee of performance for any particular engine. The data is subject to instrumentation, measurement, and engine to engine variability.
2. Test reference procedures ISO 3744 and ANSI S12.34-1998 as applicable.
3. All data are "A" weighted and are rounded to the nearest dB.
4. Engine with "typical Radiator and fam". Sound Power (dB).
5. Engine Exhaust at 1 Meter from open stack, Sound Pressure (dB).